

# DTR-30.1

7.2-CHANNEL HOME THEATRE RECEIVER



## FEATURES

### AMPLIFICATION

- 90 W/Ch, 8 Ω, 20 Hz - 20 kHz, 2 Channels Driven, FTC
- Discrete Output Stages for All Channels (4 ohms Capability)
- WRAT—Wide Range Amplifier Technology (5 Hz - 100 kHz)
- Optimum Gain Volume Circuitry
- H.C.P.S.—High Current Power Supply
- Bi-Amping Capability for Music and Movie Sound Effects

### PROCESSING

- HDMI™ (Version 1.3a to Support 1080p, Deep Color™, x.v. Color™, LipSync, Dolby TrueHD, Dolby Digital Plus, DTS-HD Master Audio, DTS-HD High Resolution Audio, DVD-Audio, Super Audio CD, Multichannel PCM)
- HDMI Video Upscaling (to 1080i) with Faroudja DCDi Edge™\*1
- Dolby® TrueHD, Dolby® Digital Plus and Dolby® Pro Logic IIz Decoding
- DTS-HD® Master Audio, DTS-HD® High-Resolution Audio Decoding
- Advanced TI (Aureus™) 32-bit Processing DSP Chip
- 192 kHz/24-Bit Audio DACs for All Channels
- Audyssey 2EQ™ Automatic Room Calibration and Correction
- Audyssey Dynamic EQ™ for Loudness Correction
- Audyssey Dynamic Volume™ for Optimal Listening Levels and Dynamic Range
- 4 DSP Modes for Gaming (Rock, Sports, Action, RPG)
- A-Form Listening Mode Memory and IntelliVolume Input Level Calibration System
- Music Optimiser for Compressed Music Files
- Auto Input Detect Function
- Independent Crossover Adjustment for F/C/S/SB
- A/V Synchronisation Function (up to 100 ms in 5 ms Steps)

\*1 From component video and composite video inputs via HDMI output

### CONNECTIONS

- HDMI (6 Inputs (1 on Front Panel) and 1 Output)
- HDTV-Capable (720p/1080i) Component Video Switching (2 Inputs and 1 Output)
- Universal Port for Single-Cable Connection of Optional Onkyo UP-A1 Dock for the iPod & UP-DT1 (DAB+ Tuner Module)
- Colour-Coded 7.2-Multichannel Pre Outs
- Assignable Digital Inputs (2 Optical/2 Coaxial)
- Front Panel A/V Inputs

### CUSTOM INTEGRATION FEATURES

- Bi-directional Ethernet & RS232 Port for Control Systems
- Powered Zone 2 and Zone 2 Pre Out; Independent Control for Balance and Bass/Treble
- Max & Power On Volume Settings for Main Zone & Zone 2
- IntelliZone for Second Room Playback and Control
- Dealer Settings Memory Store & Recall with Lock/Unlock
- Permanently Stored Memory Settings
- Multi-Language OSD (English, French, German, Spanish)
- 2 IR Inputs and 1 Output
- 3 Unique Assignable IR Code Sets
- 3 Programmable 12V Triggers (with Adjustable Delay)
- RIHD (Remote Interactive over HDMI) for Integrated System Control\*2 (Compatible with Leading Brand-Name Devices, Including Those with Panasonic Viera Link™ and Toshiba REGZA LINK™, and Selected Sharp Displays)
- PreProgrammed RI Remote Control with OSD Set-up

\*2 Compatibility depends on respective model



**HDMI**

**DOLBY**  
TRUE HD  
PRO LOGIC IIz

**dts-HD**  
Master Audio

FAROUDJA  
DCI | EDGE

CINEMA FILTER

WRAT  
WIDE RANGE AMP TECHNOLOGY

192 kHz/24 bit

AUDYSSEY  
2EO  
DYNAMIC EQ  
DYNAMIC VOLUME

POWER PREZEE

RIHD

Theater-Dimensional

MUSIC OPTIMIZER

CERTIFIED  
CRESTRON  
Integrated Partner

### SPECIFICATIONS

#### AMPLIFIER

Power Output

All Channels:

175 W @ 6 Ω, 1 kHz,  
1 Channel Driven, JEITA  
90 W @ 8 ohms, 20 Hz—20 kHz,  
2 Channel Driven, FTC

Dynamic Power Output (Stereo): 2 × 210 W at 3 Ω  
2 × 180 W at 4 Ω  
2 × 110 W at 8 Ω

Frequency Response: 5 Hz to 100 kHz: +1/−3 dB  
(Direct Mode)

Signal-to-Noise Ratio: 106 dB (LINE, IHF-A)

Total Harmonic Distortion: 0.08% (1 kHz, 1W)

Damping Factor: 60 (Front, 1 kHz, 8 Ω)

Speaker impedance: 4 Ω—16 Ω

#### INPUT SENSITIVITY AND IMPEDANCE

Line: 200 mV, 47 kΩ

#### OUTPUT LEVEL AND IMPEDANCE

Rec Out: 200 mV, 2.2 kΩ

#### TONE CONTROL

Bass: ±10 dB at 50 Hz

Treble: ±10 dB at 20 kHz

#### FM

Tuning Range: 87.5-108 MHz

#### AM

Tuning Range: 522-1,611 kHz  
530-1,170 kHz



#### GENERAL

Power supply: AC 230 V, 50 Hz

Power consumption: 550 W

Dimensions (W × H × D): 435 × 175 × 326.5 mm

Weight: 10.9 kg



Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Dolby, Pro Logic, and the double-D symbol are registered trademarks of Dolby Laboratories. DTS is a registered trademark & the DTS logo and Symbol are trademarks of DTS, Inc. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. Faroudja DCI Edge is a registered trademark of Genesis Microchip Inc. All rights reserved. Manufactured under license from Audyssey Laboratories. U.S. and foreign patents pending. 2EQ, Dynamic EQ, and Dynamic Volume are trademarks of Audyssey Laboratories. The trademark of Apple Inc., registered in the U.S. and other countries. Aureus is a trademark of Texas Instruments. x.v.Color is a trademark of Sony Corporation. WRAT, Theater-Dimensional, CinemaFILTER and Music Optimizer are trademarks of Onkyo Corporation. All other trademarks and registered trademarks are the property of their respective holders.

**Australia: Sole Distributor, Amber Technology Ltd.**  
Unit B, 5 Skyline Place, Frenchs Forest NSW 2086, Sydney, AUSTRALIA  
Tel: +61-2-9452-8600 Fax: +61-2-9972-7143  
<http://www.ambertech.com.au>  
e-mail: [consumer@ambertech.com.au](mailto:consumer@ambertech.com.au)